





# uVision<sup>™</sup> 365 STANDARD SERIES

IP Rated, Fanless LED UV-A Inspection Lamps

Also Available UV-365ES, UV-365EH, & UV-365MEH

ALE MO

- Compact, cost-effective handheld inspection lamps
- > Available in two intensities to suit your specific needs: standard-intensity & high-intensity
- > Can be used in forensics, specialty UV applications, and NDT/NDE
- Mobile AC/DC version available!

FOR FLUORESCENT INSPECTION

**IN ANY INDOOR / OUTDOOR** 

**3 UV-A LEDS** ---For wide and even area of coverage

**ENVIRONMENT** 





Fanless & Cool Running

uVision<sup>™</sup> 365



Lightweight & Rugged

### FANLESS DESIGN

Maintains optimum lamp temperature using state-ofthe-art heat sinks

> **PISTOL GRIP** Comfortable, balanced control

WHITE LIGHT LED Allows for scanning surface flaws

> LONG-LASTING UV-A LENSES Reduce the rate of solarization

EASY CONTROL Grip-mounted, three-way rocker switch (white light/off/UV)




## uVision<sup>™</sup> 365 UV-365 STANDARD SERIES

MODEL	UV-A	INAL STEADY-STATE (365 nm) INTENSITY at 15 in (38 cm)	VISIBLE LIGHT MEASUREMENT	<b>UV-A COVERAGE AREA</b> at 15 in (38 cm) at minimum 1,200 µW/cm <sup>2</sup>	AC/DC MOBILE Version
UV-365ES*		4,700 µW/cm <sup>2</sup>	< 1 foot-candle (11 lux)	6 in (15.24 cm) Diameter	
UV-365EH*		7,000 µW/cm <sup>2</sup>	< 1 foot-candle (11 lux)	7 in (17.78 cm) Diameter	
UV-365MEH*		7,000 µW/cm <sup>2</sup>	< 1 foot-candle (11 lux)	7 in (17.78 cm) Diameter	
		(3) UV-A LEDs, (1) white light LED Pistol grip			
Lamp Head Diameter:		3.3 in (8.38 cm)			
Height:		7.5 in (19 cm)			
Width:		3.5 in (8.9 cm)			SPECTROLINE
Weight:		1.7 lb (0.73 kg) (without battery pack)		LINUERAIL OF LINES UNDER AN AUTOMATION AND AUTOMATION AUTOMATICA	
White Light LED Intensity:		400 foot-candles (4,306 lux)		Product Name - stillshafe" MD3 Mander Monolly KC torins Product Name - <u>VESTRE</u>	
Power Requirements:		100-120VAC / 12VDC (Also available in 230V & 240V versions)			135 linkelig voldegt 233 me
Battery Pack:				ion™ 365 C Mobile Kit	

 $\Phi$  UV-A intensity reading taken with the Spectroline® AccuMAXTM Series meter, and is factory set to the value shown.


\*Each lamp is fitted with an 8-foot cord and the appropriate plug for the country of destination. An optional 20-foot cord is available. The "/20" suffix denotes the 20-foot power cord options.



Lamp with AC power supply, UV-absorbing spectacles, battery pack with 12V rechargeable NiMH battery, comes in a padded case.

#### CERTIFICATE OF LIGHT OUTPUT

#### UV-A Beam Profiles





DISTRIBUTED BY:



800-900-9097 info@NDTUnlimited.com www.NDTUnlimited.com